



## **AENLED/LI/3M/ST**

EndLED Lithium Exit Sign 2.5W Maintained / Non-Maintained White



## **Features**

Low profile compact and modern polycarbonate LED exit sign

LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime

Self-test emergency as standard

Supplied with all legend options - arrow down, arrow up and arrow left/right

20mm top and rear cable entries

Viewing distance 30 metres

## General Information

Lamp Type	LED
Colour / Finish	White
Self Test	Yes
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Surface
Warranty (Years)	5
CE Mark	Yes
Width (mm)	316
Height (mm)	180
Depth (mm)	33
Accessories	ASBP/18

## Technical Information

Wattage	2.5W
Lumens Delivered	18lm (Emergency)
CCT	6000K
Input	220-240V
Hertz	50Hz
Operating Temp	5C° to 40C°

## Technical Data - ETIM - Emergency luminaire (EC001957)

<b>Mounting method</b>	Wall surface mounted
<b>Function</b>	Escape route signage
<b>Monitoring equipment</b>	Automatic self test
<b>With light source</b>	Yes
<b>Material housing</b>	Plastic
<b>Colour housing</b>	White
<b>Nominal voltage</b>	220-240 V
<b>Degree of protection (IP)</b>	IP20
<b>Protection class</b>	II
<b>Max. system power</b>	2.5 W
<b>Colour temperature</b>	6000-6000 K
<b>Recognition distance</b>	30 m
<b>Width</b>	33 mm
<b>Height/depth</b>	180 mm
<b>Length</b>	316 mm

Datasheet generated from <https://onetimepim.com> last updated Tuesday, June 23, 2020 10:43:42 AM

