


## Metallic conduit systems

### Type B & C90 - Adaptasteel

#### Type B - Adaptasteel

Straight fitting - Swivel external thread / Materials: Nickel plated brass

|   | Part no.   | Nominal conduit size |               | Part no.    | Nominal conduit size |           |
|---|------------|----------------------|---------------|-------------|----------------------|-----------|
|   |            | (mm)                 | Metric thread |             | (mm)                 | PG thread |
|  | SP10/M12/B | 10                   | M12           | SP10/PG7/B  | 10                   | PG7       |
|   | SP12/M16/B | 12                   | M16           | SP12/PG9/B  | 12                   | PG9       |
|   | SP16/M16/B | 16                   | M16           | SP16/PG11/B | 16                   | PG11      |
|   | SP16/M20/B | 16                   | M20           | -           | -                    | -         |
|   | SP20/M20/B | 20                   | M20           | SP20/PG16/B | 20                   | PG16      |
|   | SP25/M25/B | 25                   | M25           | SP25/PG21/B | 25                   | PG21      |
|   | SP32/M32/B | 32                   | M32           | SP32/PG29/B | 32                   | PG29      |
|   | SP40/M40/B | 40                   | M40           | SP40/PG36/B | 40                   | PG36      |
|   | SP50/M50/B | 50                   | M50           | SP50/PG42/B | 50                   | PG42      |

For insertion into threaded entries & knockouts using a locknut (order locknut separately)

#### Approvals



#### IP rating

For use with: Type SP / SN / LFH-SP

| IP rating | Appropriate conduit |
|-----------|---------------------|
| IP54      | Yes                 |
| IP65      | N/A                 |
| IP66      | N/A                 |
| IP67      | N/A                 |
| IP68      | N/A                 |
| IP69      | N/A                 |

#### Temperature range


Static applications: -50°C to +300°C  
Moving applications: -45°C to +250°C

#### Fitting characteristics



#### Type C90 - Adaptasteel

90° Combined fitting & elbow / Materials: Nickel plated brass

|  | Part no.     | Nominal conduit size |               |
|--|--------------|----------------------|---------------|
|  |              | (mm)                 | Metric thread |
|  | SP16/M16/C90 | 16                   | M16           |
|  | SP16/M20/C90 | 16                   | M20           |
|  | SP20/M20/C90 | 20                   | M20           |
|  | SP25/M25/C90 | 25                   | M25           |
|  | SP32/M32/C90 | 32                   | M32           |

For insertion into threaded entries & knockouts using a locknut (order locknut separately)

#### Approvals



#### IP rating

For use with: Type S / SS

| IP rating | Appropriate conduit |
|-----------|---------------------|
| IP54      | N/A                 |
| IP65      | Yes                 |
| IP66      | N/A                 |
| IP67      | N/A                 |
| IP68      | N/A                 |
| IP69      | N/A                 |

#### Temperature range

Static applications: -50°C to +300°C  
Moving applications: -45°C to +250°C

#### Fitting characteristics

