


## Metallic conduit systems

### Type M & F - Adaptasteel

#### Type M - Adaptasteel

#### Straight swivel fitting - External male thread / Materials: Nickel plated brass



| Part no.   | Nominal conduit size (mm) | Metric thread |
|------------|---------------------------|---------------|
| SP12/M16/M | 12                        | M16           |
| SP16/M16/M | 16                        | M16           |
| SP16/M20/M | 16                        | M20           |
| SP20/M20/M | 20                        | M20           |
| SP25/M25/M | 25                        | M25           |
| SP32/M32/M | 32                        | M32           |
| SP40/M40/M | 40                        | M40           |
| SP50/M50/M | 50                        | M50           |

| Part no.   | Nominal conduit size (mm) | NPT thread |
|------------|---------------------------|------------|
| SP16/038/M | 16                        | 3/8"       |
| SP20/050/M | 20                        | 1/2"       |
| SP25/075/M | 25                        | 3/4"       |
| SP32/100/M | 32                        | 1"         |

For insertion into threaded entries & knockouts using a locknut (order locknut separately)

| Part no.    | Nominal conduit size (mm) | PG thread |
|-------------|---------------------------|-----------|
| SP12/PG9/M  | 12                        | PG9       |
| SP16/PG11/M | 16                        | PG11      |
| SP16/PG13/M | 16                        | PG13,5    |
| SP20/PG16/M | 20                        | PG16      |
| SP25/PG21/M | 25                        | PG21      |
| SP32/PG29/M | 32                        | PG29      |

#### Approvals



#### IP rating

#### Appropriate conduit

For use with: Type SP / SN / LFH-SP

|      |     |
|------|-----|
| IP54 | N/A |
| IP65 | Yes |
| IP66 | N/A |
| IP67 | N/A |
| IP68 | N/A |
| IP69 | N/A |

#### Temperature range

Static applications: -50°C to +300°C

Moving applications: -45°C to +250°C

#### Fitting characteristics



#### Type F - Adaptasteel

#### Straight fitting - Fixed internal female thread / Materials: Nickel plated brass



| Part no.   | Nominal conduit size (mm) | Metric thread |
|------------|---------------------------|---------------|
| SP20/M20/F | 20                        | M20           |
| SP25/M25/F | 25                        | M25           |
| SP32/M32/F | 32                        | M32           |

For external threads and other fittings

#### Approvals



#### IP rating

#### Appropriate conduit

For use with: Type SP / SN / LFH-SP

|      |     |
|------|-----|
| IP54 | Yes |
| IP65 | N/A |
| IP66 | N/A |
| IP67 | N/A |
| IP68 | N/A |
| IP69 | N/A |

#### Temperature range

Static applications: -50°C to +300°C

Moving applications: -45°C to +250°C