

## Non-metallic conduit systems

### Type SA & CS90 - Adaptalok

#### Type SA - Adaptalok

Straight fitting - Swivel external male thread / Materials: Polyamide (nylon) 66, Nickel Plated Brass Thread / Colour: Black (BL), Grey (GR)

Part no.	Nominal conduit size (mm)	Metric thread	Part no.	Nominal conduit size (mm)	PG thread
AL13/M16/SA*	13	M16	AL13/PG9/SA*	13	PG9
AL16/M16/SA	16	M16	AL16/PG11/SA	16	PG11
AL21/M20/SA	21	M20	AL21/PG13/SA	21	PG13,5
-	-	-	AL21/PG16/SA	21	PG16
AL28/M25/SA	28	M25	AL28/PG21/SA	28	PG21
AL34/M32/SA	34	M32	AL34/PG29/SA	34	PG29
AL42/M40/SA	42	M40	AL42/PG36/SA	42	PG36
AL54/M50/SA	54	M50	AL54/PG48/SA	54	PG48
AL54/M63/SA	54	M63	-	-	-



For insertion into threaded entries & knockouts using a locknut. Order locknut separately  
To order quote part number & body colour, e.g. AL13/M16/SA/BL. NPT also available  
\*These parts are not covered by the RU certification

#### Approvals



#### IP rating      Appropriate conduit

For use with: Type PA / CP / PR / PF	
IP66	Yes
IP67	Yes + ALS Seal
IP68	Yes + ALS Seal
IP69	Yes + ALS Seal

#### Temperature range

Static applications: -50°C to +120°C  
Moving applications: -45°C to +120°C

#### Fitting characteristics



#### Type CS90 - Adaptalok

90° Elbow fitting - Swivel external male thread / Materials: Polyamide (nylon) 66, nickel plated brass thread / Colour: Black (BL), Grey (GR)

Part no.	Nominal conduit size (mm)	Metric thread	Part no.	Nominal conduit size (mm)	PG thread
AL13/M16/CS90*	13	M16	AL13/PG9/CS90*	13	PG9
AL16/M16/CS90	16	M16	AL16/PG11/CS90	16	PG11
AL21/M20/CS90	21	M20	AL21/PG13/CS90	21	PG13,5
-	-	-	AL21/PG16/CS90	21	PG16
AL28/M25/CS90	28	M25	AL28/PG21/CS90	28	PG21
AL34/M32/CS90	34	M32	AL34/PG29/CS90	34	PG29
AL42/M40/CS90	42	M40	AL42/PG36/CS90	42	PG36
AL54/M50/CS90	54	M50	AL54/PG48/CS90	54	PG48
AL54/M63/CS90	54	M63	-	-	-



For insertion into threaded entries & knockouts using a locknut. Order locknut separately  
To order quote part number & body colour, e.g. AL13/M16/CS90/BL. NPT also available  
\*These parts are not covered by the RU certification

#### Approvals



#### IP rating      Appropriate conduit

For use with: Type PA / CP / PR / PF	
IP66	Yes
IP67	Yes + ALS Seal
IP68	Yes + ALS Seal
IP69	Yes + ALS Seal

#### Temperature range

Static applications: -50°C to +120°C  
Moving applications: -45°C to +120°C

#### Fitting characteristics

