


Metallic conduit systems

EMI screen Type A & B - Adaptasteel

Type A - Adaptasteel

Straight fitting - Fixed External male thread / Materials: Nickel plated brass

	Part no.	Nominal conduit size (mm)	Metric thread
	SB10/M12/A	10	M12
	SB12/M16/A	12	M16
	SB16/M16/A	16	M16
	SB20/M20/A	20	M20
	SB25/M25/A	25	M25
	SB32/M32/A	32	M32
	SB40/M40/A	40	M40
	SB50/M50/A	50	M50
	SB63/M63/A	63	M63
	SB75/M75/A	75	M75

For insertion into knockouts using a locknut (order locknuts separately)

Approvals



IP rating

Appropriate conduit

For use with: Type SB / STC / SSB / SSBGS

IP40	Yes
IP65	N/A
IP66	N/A
IP67	N/A
IP68	N/A
IP69	N/A


Temperature range

Static applications: -50°C to +300°C

Moving applications: -45°C to +250°C

Type B - Adaptasteel

Straight fitting - Swivel external male thread / Materials: Nickel plated brass

	Part no.	Nominal conduit size (mm)	Metric thread
	SB10/M12/B	10	M12
	SB12/M16/B	12	M16
	SB16/M16/B	16	M16
	SB20/M20/B	20	M20
	SB25/M25/B	25	M25
	SB32/M32/B	32	M32
	SB40/M40/B	40	M40
	SB50/M50/B	50	M50

For insertion into threaded entries & knockouts using a locknut (order locknut separately)

Approvals



IP rating

Appropriate conduit

For use with: Type SB / STC / SSB / SSBGS

IP40	Yes
IP65	N/A
IP66	N/A
IP67	N/A
IP68	N/A
IP69	N/A

Temperature range

Static applications: -50°C to +300°C

Moving applications: -45°C to +250°C

Fitting characteristics

