


Non-metallic conduit systems




Type A & C90 - Adapting

Type A - Adapting

Straight fitting - Fixed external male thread / Materials: Polyamide (nylon) 66 & acetal (POM) / Colour: Black (BL) Only


	Part no.	Nominal conduit size		Part no.	Nominal conduit size	
		(mm)	Metric thread		(mm)	PG thread
	AR13/M16/A	13	M16	AR13/PG9/A	13	PG9
	AR16/M16/A	16	M16	AR16/PG11/A	16	PG11
	AR16/M20/A	16	M20	AR16/PG13/A	16	PG13,5
	AR21/M20/A	21	M20	AR21/PG16/A	21	PG16
	AR28/M25/A	28	M25	AR28/PG21/A	28	PG21
	AR34/M32/A	34	M32	AR34/PG29/A	34	PG29
	AR42/M40/A	42	M40	AR42/PG36/A	42	PG36
	AR54/M50/A	54	M50	AR54/PG48/A	54	PG48

For insertion into threaded entries & knockouts. Locknut supplied with METRIC THREAD ONLY
To order quote part number, e.g. AR21/M20/A/BL
PF & NPT thread sizes available




Approvals	IP rating	Appropriate conduit	Temperature range	
 	For use with: Type PA / CP / PR / PF		Static applications: -40°C to +120°C	
	IP40	Yes	Moving applications: -5°C to +120°C	
	IP65	N/A	Fitting characteristics	
	IP66	N/A		
	IP67	N/A		
	IP68	N/A		
	IP69	N/A		

Type C90 - Adapting

90° Elbow fitting - Fixed external male thread / Materials: Polyamide (nylon) 66, nickel plated brass thread/TPE Colour: Black (BL), Grey (GR) / Yellow (Y) Elastomer

	Part no.	Nominal conduit size	
		(mm)	Metric thread
	AR13/M16/C90	13	M16
	AR16/M16/C90	16	M16
	AR16/M20/C90	16	M20
	AR21/M20/C90	21	M20
	AR28/M25/C90	28	M25
	AR34/M32/C90	34	M32
	AR42/M40/C90	42	M40
	AR54/M50/C90	54	M50

For insertion into knockouts. Locknut supplied with METRIC THREAD ONLY
To order quote part number & body colour, e.g. AR21/M20/C90/BL
PF & NPT thread sizes available

Approvals	IP rating	Appropriate conduit	Temperature range	
 	For use with: Type PA / CP / PR / PF		Static applications: -40°C to +120°C	
	IP40	Yes	Moving applications: -5°C to +120°C	
	IP65	N/A	Fitting characteristics	
	IP66	N/A		
	IP67	N/A		
	IP68	N/A		
	IP69	N/A		