


Metallic conduit systems

Type C & E - Adaptasteel

Type C - Adaptasteel

Smooth entry bush / Materials: Nickel plated brass

	Part no.	Nominal conduit size (mm)	Hole size (mm)
	SP10/9/C	10	9
	SP12/12/C	12	12
	SP16/16/C	16	16
	SP20/20/C	20	20
	SP25/25/C	25	25
	SP32/32/C	32	32
	SP40/40/C	40	40
	SP50/51/C	50	51
	SP63/61/C	63	61
	SP75/75/C	75	75

For locking conduit into plain holes in enclosures

Approvals



IP rating

Appropriate conduit

Temperature range

For use with: Type SP / SN / LFH-SP


Static applications: -50°C to +300°C

IP54	Yes
IP65	N/A
IP66	N/A
IP67	N/A
IP68	N/A
IP69	N/A

Moving applications: -45°C to +250°C

Type E - Adaptasteel

Conduit terminator / Materials: Nickel plated brass

	Part no.	Nominal conduit size (mm)
	SP12/E	12
	SP16/E	16
	SP20/E	20
	SP25/E	25
	SP32/E	32
	SP40/E	40
	SP50/E	50

Cable Protection at exit point

Approvals



IP rating

Appropriate conduit

Temperature range

For use with: Type SP / SN / LFH-SP

Static applications: -50°C to +300°C

IP54	Yes
IP65	N/A
IP66	N/A
IP67	N/A
IP68	N/A
IP69	N/A

Moving applications: -45°C to +250°C