

Non-metallic conduit systems

Type A - Adaptalok

Type A - Adaptalok

Straight fitting - Fixed external male thread / Materials: Polyamide (nylon) 66 / Colour: Black (BL), Grey (GR)



Part no.	Nominal conduit size (mm)	Metric thread
AL10/M12/A*	10	M16
-	-	-
AL13/M16/A*	13	M16
AL13/M20/A*	13	M20
-	-	-
AL16/M16/A	16	M16
AL16/M20/A	16	M20
-	-	-
-	-	-
AL21/M20/A	21	M20
-	-	-
AL21/M25/A	21	M25
AL28/M25/A	28	M25
AL28/M32/A	28	M32
AL34/M32/A	34	M32
AL34/M40/A	34	M40
AL42/M40/A	42	M40
AL42/M50/A	42	M50
AL54/M50/A	54	M50
AL54/M63/A	54	M63

Part no.	Nominal conduit size (mm)	PG thread
AL10/PG7/A*	10	PG7
AL10/PG9/A*	10	PG9
AL13/PG9/A*	13	PG9
AL13/PG11/A*	13	PG11
AL13/PG13/A*	13	PG13,5
AL16/PG9/A	16	PG9
AL16/PG11/A	16	PG11
AL16/PG13/A	16	PG13,5
AL16/PG16/A	16	PG16
AL21/PG11/A	21	PG11
AL21/PG13/A	21	PG13,5
AL21/PG16/A	21	PG16
AL28/PG21/A	28	PG21
-	-	-
AL34/PG29/A	34	PG29
-	-	-
AL42/PG36/A	42	PG36
-	-	-
AL54/PG48/A	54	PG48
-	-	-

Part no.	Nominal conduit size (mm)	PF thread
AL10/PF025/A*	10	1/4"
AL13/PF038/A*	13	3/8"
AL16/PF038/A	16	3/8"
AL16/PF050/A	16	1/2"
AL21/PF050/A	21	1/2"
AL28/PF075/A	28	3/4"
AL34/PF100/A	34	1"
AL42/PF125/A	42	1 1/4"
AL54/PF150/A	54	1 1/2"
AL54/PF200/A	54	2"

Part no.	Nominal conduit size (mm)	NPT thread (in)
-	-	-
AL13/038/A*	13	3/8"
AL16/038/A	16	3/8"
AL16/050/A	16	1/2"
AL21/050/A	21	1/2"
AL28/075/A	28	3/4"
AL34/100/A	34	1"
AL42/125/A	42	1 1/4"
AL54/150/A	54	1 1/2"
-	-	-

For insertion into knockouts using a locknut. Locknut supplied with METRIC THREAD ONLY

To order quote part number & body colour, e.g. AL10/M12/A/BL

*These parts are not covered by the RU certification

Approvals



NF

IP rating

Appropriate conduit

For use with: Type PA / CP / PR / PF

IP66	Yes
IP67	Yes + ALS Seal
IP68	Yes + ALS Seal
IP69	Yes + ALS Seal

Temperature range

Static applications: -50°C to +120°C

Moving applications: -45°C to +120°C

Fitting characteristics

