


Non-metallic conduit systems


Polypropylene Type PP & PPA - Adaptalok

Polypropylene Type PP - Adaptalok

Medium weight conduit / Materials: Polypropylene / Colour: Black (BL) Only


	Part no.	Nominal conduit size (mm)	NW conduit size (mm)	Outside diameter (mm)	Inside diameter (mm)	Min. bend radius (mm)	Reel length (m)
	PPFM13	13	10	13.0	9.8	5	50
	PPFM16	16	13	15.8	12.1	35	50
	PPFM21	21	17	21.2	16.8	40	50
	PPFM28	28	23	28.5	23.1	60	50
	PPFM34	34	29	34.5	29.1	50	50

To order quote part number, colour & reel length, e.g. PPFM16/BL/50M




Approvals	IP rating	Appropriate fitting	Temperature range	UV resistance
	For use with: Polypropylene Type PPA		Static applications: -20°C to +90°C	Medium
	IP40	N/A	Moving applications: -5°C to +105°C	
	IP65	N/A	Flexibility & fatigue life	
	IP66	Polypropylene Type PPA	High flexibility - Medium fatigue life	
	IP67	N/A		
	IP68	N/A		
	IP69	N/A		

Polypropylene Type PPA - Adaptalok

Straight fitting - Fixed external male thread / Materials: Polypropylene / Colour: Black (BL) Only

	Part no.	Nominal conduit size (mm)	Metric thread
	AL13/M16/PPA	13	M16
	AL16/M16/PPA	16	M16
	AL21/M20/PPA	21	M20
	AL28/M25/PPA	28	M25
	AL34/M32/PPA	34	M32

For insertion into knockouts using locknuts. Locknuts supplied
To order quote part number & body colour, e.g. AL21/M20/PPA/BL

Approvals	IP rating	Appropriate conduit	Temperature range	Fitting characteristics
 	For use with: Polypropylene Type PP		Static applications: -20°C to +90°C	
	IP40	N/A	Moving applications: -5°C to +105°C	
IP65	N/A	Fitting characteristics		
IP66	Yes			
IP67	N/A			
IP68	N/A			
	IP69	N/A		