



## APRILEDP/AG/CCT



### Features

220-240V IP65 LED dimmable CCT fire rated architectural downlight

Anti-glare design to create visual comfort

Supplied with matt white bezel as standard. Chrome, satin chrome and matt black bezels sold separately

Integrated switch allows installer the choice of 2700K, 3000K, 4000K or 6000K colour temperature options

Remote driver with 2x1.5mm<sup>2</sup> + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation

Detachable LED driver for fast fix install

Low profile design and remote driver allow installation into shallow ceiling voids

Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy efficiency) of Building Regulations

LED Lifespan L70 60,000 hours

## General Information

Lamp Type	LED
Colour / Finish	Matt white
Dimmable	Yes
Fire Rated	Yes
OCTO Compatibility	Smart Indoor controller
IP Rating	IP65
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Recessed
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	88
Height (mm)	80
Accessories	APRILEDPBZ/AG/WW, APRILEDPBZ/AG/BB, APRILEDPBZ/AG/CHB, APRILEDPBZ/AG/SCB, APRILEDP/TRIM

# Technical Information

---

<b>Wattage</b>	7W
<b>Lumens Delivered</b>	460lm (2700K) - 515lm (6000K)
<b>Lm/W</b>	66lm (2700K) - 74lm (6000K)
<b>Beam Angle</b>	50
<b>CRI</b>	Ra 80
<b>CCT</b>	Tunable White
<b>Input</b>	230V
<b>Hertz</b>	50/60Hz
<b>Operating Temp</b>	-5°C to 25°C

---

Datasheet generated from <https://onetimepim.com> last updated Friday, May 21, 2021 12:40:57 PM



