



**AERMLED3/120/CW**



# Features

High performance maintenance free LED panel

TPa as standard

UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort

60W panel outperforms 3x28W T5

Cool white, warm white and daylight options

White anodised aluminium frame for visual compatibility with ceiling grid

Low glare and even light distribution for multiple applications

Panel Pod Self-Test emergency option

Panel Pod sensor option

Powered by Philips

LED lifespan L80 B10 54,000 hours

## General Information

<b>Lamp Type</b>	LED
<b>Colour / Finish</b>	White
<b>IP Rating</b>	IP44
<b>Class Protection</b>	2
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Surface/Recessed/Suspended
<b>Warranty (Years)</b>	5
<b>CE Mark</b>	Yes
<b>Length (mm)</b>	1195
<b>Width (mm)</b>	595
<b>Height (mm)</b>	10
<b>Accessories</b>	AERMLD/SK, AERMLD/120/SMF

# Technical Information

---

<b>Wattage</b>	60W
<b>Lumens Delivered</b>	5800lm
<b>Lm/W</b>	98lm
<b>CRI</b>	Ra 80
<b>CCT</b>	4000K
<b>Input</b>	230V
<b>Hertz</b>	50Hz
<b>Operating Temp</b>	-20°C to 40°C

---

Datasheet generated from <https://onetimepim.com> last updated Thursday, June 17, 2021 1:17:01 PM

