

# 6.3

## Industrial switch & fusegear

### Exel 2 switch-disconnectors & switch-disconnector fuses

See page 159 for technical data and overall dimensions.

15AXTN2



#### Exel 2 switch-disconnector

Nominal rating, I <sub>e</sub> (A)	Utilisation category at U <sub>e</sub> 415V to BS EN 60947-3		250V DC rating to BS5419 DC23 (A)	Blank endplate	Poles	Eaton list number	
	AC22A (A)	AC23A (A)					
20	20	–	20 <sup>1)</sup>	EP 842	SPSN	–	
		11			–	DP	<b>15AXD2</b>
		–			–	TPN	<b>15AXTN2</b>
32	32	–	32	–	SPSN	–	
		22			–	DP	<b>30AXD2</b>
		–			–	TPN	<b>30AXTN2</b>
63	63	–	63	EP 539	SPSN	–	
		39			–	DP	<b>60AXD2</b>
		–			–	TPN	<b>60AXTN2</b>
100	100	–	100	–	SPSN	–	
		52			–	DP	<b>100AXD2</b>
		–			–	TPN	<b>100AXTN2</b>
125	125	52	–	–	TPN	<b>125AXTN2</b>	

SPSN indicates switched neutral. <sup>1)</sup>20A units are DC22.

100KXSC2F



#### Exel 2 switch-disconnector-fuse

Nominal rating, I <sub>e</sub> (A)	Utilisation category at U <sub>e</sub> 415V to BS EN 60947-3		250V DC rating to BS5419 (A)	Blank endplate fitted	Eaton HRC fuses DC23	Poles	Eaton list number	
	AC22A (A)	AC23A (A)						
20	20	–	20 <sup>1)</sup>	EP 842	20SA2	SPSN	<b>15KXSC2F<sup>2)</sup></b>	
		11				–	DP	<b>15KXDC2F</b>
		–				–	TPN	<b>15KXTNC2F</b>
32	32	–	32	–	32SB3	SPSN	<b>30KXSC2F</b>	
		22				–	DP	<b>30KXDC2F</b>
		–				–	TPN	<b>30KXTNC2F</b>
63	63	–	63	EP 539	63SB4	SPSN	<b>60KXSC2F</b>	
		39				–	DP	<b>60KXDC2F</b>
		–				–	TPN	<b>60KXTNC2F</b>
100	100	–	100	–	100SD5 <sup>2)</sup>	SPSN	<b>100KXSC2F</b>	
		52				–	DP	<b>100KXDC2F</b>
		–				–	TPN	<b>100KXTNC2F</b>
125	125	52	–	–	125SD6 <sup>2)</sup>	TPN	<b>125KXTNC2F</b>	

SPSN indicates switched neutral. <sup>1)</sup>20A units are DC22.

<sup>2)</sup>These units have dual fixings to accept SB3, SB4 and SO fuselinks. 2x M5 screws required