

The CFH range

Features

- Digital central control system gives close time and temperature control for optimised energy usage.
- Built-in electronic control system for operation over 10 heaters (maximum).
- Accurate digital temperature control.
- Seven-day timer/programmer.
- Heat output control.*
- Powerful centrifugal blowers for effective performance.
- Fan overrun facility for maximum heater efficiency.
- Easy install 'plug and play' heater connections.
- Multi-directional wall-mounting brackets.
- Heavy-duty corrosion-resistant case.

*All CFH models are controlled via the additional digital CFCH Controller.



A range of rugged, high-power electronic fan heaters designed to offer a full heating system to larger industrial environments, these wall-mounted heaters use powerful centrifugal blowers for a faster airflow in the most challenging of environments.



Model CFH120

Offered in 6kW, 9kW or 12kW, the CFH range can be controlled individually or as a system of heaters with the additional wall-mounted digital remote (CFCH), with cool blow, heat output and thermostatic control available.

All models in the range can be simply linked together using CAT 5e data cable, and have multi-directional wall-mounting brackets for the ultimate in ease of installation and control.

Controls

The CFCH controller is the hub of the system. With accurate electronic heat control, a full seven-day day timer and programmer with a selectable five-hour run-back feature for flexibility of use.



Model	Max no. heaters	Heater communication	Supply	Height A	Width B	Depth
CFCH	10	CAT 5e ethernet / RJ45	220-240V~1PN	113mm	217mm	49mm