

Cat No.	Description	Inner Carton	Outer Carton
<b>Indicator Modules - Suitable for use with all finishes</b>			
GINGR	Green	10	100
GINOR	Orange	10	100
GINRD	Red	10	100



- For use with all finishes
- Manufactured to BS 5733
- Terminal capacity 3 x 2.5mm<sup>2</sup>, 2 x 4.0mm<sup>2</sup> & 1 x 6.0mm<sup>2</sup>
- Minimum mounting box depth 25mm
- Clearly marked terminals with backed out captive screws for easy installation

### Dimmer Modules

White	Chrome	Brushed Steel	Black Nickel	Polished Brass			
GD400	GPCD400	GBSD400	GBND400	GPBD400	2-way 400W push dimmer	10	100

- Manufactured to BS EN 60669-2-1
- Minimum mounting box depth 35mm
- Suitable for tungsten lamps, low voltage transformers & mains GU10 halogen



### Fused, Flex Outlet & Blank Modules

White	Chrome	Brushed Steel	Black Nickel	Polished Brass			
GFUSE	GPCFUSE	GBSFUSE	GBNFUSE	GPBFUSE	Fuse holder	10	100
GFLEX	GPCFLEX	GBSFLEX	GBNFLEX	GPBFLEX	Flex outlet (up to 10mm)	10	100
GBLNLK	GPCBLNLK	GBSBLNLK	GBNBLNLK	GPBBLNLK	Blank module	10	100

#### Fused Outlets

- Manufactured to BS 1363 Part 4
- Terminal capacity 3 x 2.5mm<sup>2</sup>, 2 x 4.0mm<sup>2</sup> & 1 x 6.0mm<sup>2</sup>
- Minimum mounting box depth 25mm
- Clearly marked terminals with backed out captive screws for easy installation
- Supplied with 13A fuse fitted to BS 1362

#### Flex Outlets

- Manufactured to BS 5733
- Minimum mounting box depth 35mm
- Cable entry with cord grip
- Suitable for cables with an outside diameter up to 10mm

