


CW - CABLE GLANDS

Description:

Gland that provides environmental seal on the cable outer sheath. Also provides mechanical cable retention & electrical continuity via armoured wire termination in indoor and outdoor area with all types of SWA cable.

Seal Material:

LSOH Silicone Seal & LSOH Nylon Washer



CW20S

OTHER ADDITIONAL INFORMATION



Gland Selection Chart and sizing information on next page.



Gland Selection Chart

Size	Standard Thread Size "C"		Optional Thread		Thread Length "D"	Cable Dia. "A" Max.	Cable Dia. "B"		Armour Wire Dia.	Protrusion Length "F"	A/F	A/C
	Metric	NPT	Metric	NPT			Min.	Max.				
20s16	20	½"	25	¾"	10.00	9.00	6.10	13.10	0.90	42.40	24.00	26.20
20S	20	½"	25	¾"	10.00	12.00	9.50	15.90	0.9-1.25	42.40	24.00	26.20
20	20	½"	25	¾"	10.00	14.20	12.50	20.90	0.9-1.25	45.40	30.00	33.00
25S	25	¾"	32	1"	10.00	20.00	14.00	22.00	1.20-1.60	52.60	36.00	39.20
25	25	¾"	32	1"	10.00	20.00	19.90	26.20	1.20-1.60	52.60	36.00	39.20
32	32	1"	40	1½"	10.00	27.00	23.70	33.90	1.60-2.00	53.00	46.00	50.60
40	40	1¼"	50	1½"	15.00	33.00	27.90	40.40	1.60-2.00	55.60	55.00	60.00
50S	50	1½"	63	2"	15.00	38.50	35.20	46.70	2.00-2.50	54.50	60.00	65.00
50	50	2"	63	2½"	15.00	44.30	40.40	53.00	2.00-2.50	54.00	70.00	75.00
63S	63	2"	75	2½"	15.00	50.50	45.60	59.40	2.50	56.70	75.00	80.00
63	63	2½"	75	3"	15.00	56.50	54.60	65.80	2.50	59.00	80.00	85.00
75S	75	2½"	90	3"	15.00	62.50	59.00	72.00	2.50	65.50	90.00	95.00
75	75	3"	90	3½"	15.00	68.30	66.70	78.40	2.50	67.70	100.00	110.00
90	90	3½"	100	4"	20.00	80.50	76.20	90.30	2.50-3.15	87.50	112.00	122.00

