

FFP1W/FFP2W - WARRIOR DUST MASKS

Description:

General purpose masks, suited to most industrial applications

Size:

One Size

Colour Range:

FFP1W - White, yellow elastic

FFP2W - White, blue elastic



FFP1W/FFP2W

ADDITIONAL INFORMATION

- The instructions for use must be read and taken into consideration. Failure to comply with the instructions for use and the information contained therein can represent a health risk and can lead to irreversible damage to health.
- The user must be conversant with the use and maintenance of the device.
- The oxygen content in the breathing air must be at least 17 volume %.
- Non-aerated containers, excavations, ducts and small areas may not be entered with particle-filtering half masks.
- Not to be worn during grit-blasting work.
- Nature and concentration of hazardous substances must be known.
- Particle-filtering half masks do not protect against gases and vapours.
- In the event of unpleasant difficulty in breathing, the mask must be changed.
- The duration of use may not exceed a single work shift.
- Respiratory protection devices are unsuitable for individuals with beards sideburns or deep scarring in the area around the edge line of the respiratory protection device.
- In the event of a risk of oxygen shortage, excessively high concentrations of hazardous substances or unknown ratios, insulation devices operating independently of the environment must be employed.



STORAGE

Storage or warehouse areas must have a normal climate, i.e. the air must be dry, cool and free from hazardous substances. In addition, the masks must be protected against light and heat radiation.

Unpacked or damaged masks may no longer be used. The storage period, under these conditions, is limited to 5 years.

CHECK BEFORE USE

A respiratory protection device selected according to the working conditions is essential to protect your health. Before you use these products, you must ensure, for example consulting a qualified person, whether this product offers sufficient protection against the hazardous substances in the working environment. If you are suffering from any illness or other symptoms, consult a physician about the reliability of using respiratory protection devices.

TECHNICAL DETAILS

EN 149:20DI+A 1:2009
Protection level FFP1/FFP2

LIMITS OF USE

The mask must be replaced after a maximum of B hours use or if, due to the effect of dust penetration, breathing resistance becomes too considerable, or immediately leave the work area if:

- Breathing becomes difficult
- A feeling of dizziness or other irritation occurs.
- The mask is damaged.
- An emergency occurs.

DELIGO