



Ducting & Accessories

Round (F) 125mm to Rectangular (F) Adaptor



Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
370127	204 x 60	140	210	213	<1	<1	1.5	2.8	4.5	6.7	9	11.5

Round (F) 150mm to Rectangular (F) Adaptor




Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate						
		A	B	C	60 l/s	120 l/s	180 l/s	240 l/s	300 l/s	360 l/s	
403031	220 x 90	160	225	203	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Short Round (M) 100mm to 110 x 54 (F) Adaptor



Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
455035	110 x 54	60	110	105	1.2	4.3	8.4	20	30.2	43	62	88


Round 2m Ducting length Insulated/Uninsulated



Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate							
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s
406873	Insulated 100 Ø*	200	200	2000	<1	<1	1.7	2.8	3.6	4.5	5.3	6.2
5108250	Uninsulated 100 Ø	100	100	2000	<1	<1	1.7	2.8	3.6	4.5	5.3	6.2
406874	Insulated 125 Ø*	225	225	2000	<1	<1	<1	1.3	1.8	2.4	3.1	3.8
434715*	Uninsulated 125 Ø	125	125	1500	<1	<1	<1	1.3	1.8	2.4	3.1	3.8
406875	Insulated 150 Ø*	265	265	2000	<1	<1	<1	<1	1.2	1.6	2	2.5
5108248	Uninsulated 150 Ø	150	150	2000	<1	<1	<1	<	1.2	1.6	2	2.5

#1.5 metres

Equal Tee Insulated/Uninsulated MMM



Stock Ref	Duct Size	External Dimensions (mm)			Resistance (Pa) at flow rate								
		A	B	C	8 l/s	13 l/s	21 l/s	29 l/s	37 l/s	45 l/s	53 l/s	61 l/s	
406884	Insulated 100 Ø*	290	210	235									
372007	Uninsulated 100 Ø	190	110	135									
406885	Insulated 125 Ø*	310	215	260									
428636	Uninsulated 125 Ø	210	115	160									
406886	Insulated 150 Ø*	335	245	285									
370237	Uninsulated 150 Ø	235	130	177									

*Minimum insulation wall thickness 25mm. Insulation Thermal Conductivity: 0.04 W/(m.K)