










INEXPENSIVE EXTENSION OF THE DETECTION AREA WITH SLAVE OCCUPANCY DETECTORS

Occupancy detector	Page				Clip	Daylight appraisal	Motion detection	Remote controllable	Range	Additional functions
PD1N-S	74	92878	92875	92872	–	–	■	–	7.50 x 7.50 m	Square area
PD2-S	75	92152	92166	92156	–	–	■	–	Ø 10 m	–
PD4-S	76	92142	92254	92163	–	–	■	–	Ø 24 m	–
PD4-S-C	77	92442	92444	92445	–	–	■	–	max. Ø 40 m	Corridor detector
PD4-S-GH	78	92265	–	–	–	–	■	–	Ø 44 m	High elevations
PD5-S	79	–	–	–	92316	–	■	–	Ø 10 m	For T8 and T5 fluorescent lamps
PD9-S	80	–	92905 – white 92906 – silver	–	–	–	■	–	Ø 10 m	Mini detector
PD9-S-GH	81	–	92928 – white 92929 – silver	–	–	–	■	–	Ø 6 m	High elevations
PD9-S-SDB	50	–	92915	–	–	–	■	–	Ø 10 m	Mini detector
PD9-S-SDB-GH	51	–	92933	–	–	–	■	–	Ø 6 m	High elevations




11-48 V OCCUPANCY DETECTORS

Occupancy detector	Page				Clip	Daylight appraisal	Motion detection	Remote controllable	Range	Additional functions
PD2-M-2C-11-48V-3A	82	92154	92164	–	–	■	■	■	Ø 24 m	3 A version
PD2-M-2C-11-48V-RR	82	92305	92306	–	–	■	■	■	Ø 24 m	with reed relay

OCCUPANCY DETECTORS FOR KNX/EIB BUS FOR SWITCHING OR DIMMING

Occupancy detector	Page				Clip	Daylight appraisal	Motion detection	Remote controllable	Range	Additional functions
PD2-DIM-KNX/EIB	83	92430	92431	92432	–	■	■	–	Ø 10 m	For dimming
PD4-DIM-KNX/EIB	84	92433	92434	92435	–	■	■	–	Ø 24 m	For dimming
PD4-DIM-KNX/EIB-GH	85	92454	–	–	–	■	■	–	Ø 44 m	High elevations
PD4-DIM-KNX/EIB-C	86	92461	92456	92459	–	■	■	–	max. Ø 40 m	For dimming
PD9-DIM-KNX/EIB	87	–	92437	–	–	■	■	–	Ø 10 m	For dimming

OCCUPANCY DETECTORS FOR LON BUS

Occupancy detector	Page				Clip	Daylight appraisal	Motion detection	Remote controllable	Range	Additional functions
PD2-LON	88	92300	92301	–	–	■	■	■	Ø 10 m	–
PD9-LON	89	–	92930	–	–	■	■	■	Ø 10 m	Mini detector

