FJSE G

## Order Code : 94 FO SB-W Cheriton Victorian Satin Brass 1 gang 13A Fuse Only. Standard Insert will be Satin Brass with a White surround.

## Attributes

Primary Range FO Insrt Plate material Metal 88mm Size (single) height Size (single) width 88mm Size (single) depth 8.5mm Box fixing hole centres 60.3mm Grid fixing hole centres Minimum wall box depth 35mm Current rating 13 Amp Voltage Max load 13 Amp IP rating IP2XD Switched Poles none Contact Gap Minimum none Terminal Capacity 1 5 x 1mm2 **Terminal Capacity 2** Terminal Capacity 3 **Terminal Capacity 4 Terminal Capacity 5** 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 1 x 6mm2 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature **Recommended Location** Max installation Altitude 2000m **BS EN ISO Standard** Patents And Trademarks Trade Mark No. 2344779

Cheriton Victorian Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue 220/250V AC 4 x 1.5mm2 3 x 2.5mm2 1 x 4mm2 Multi-Strand 3 x 2.5mm2 2 x 4mm2 Multi-Strand Must be earthed -5° to +40°C Indoor use only BS 1363-4

All products listed conform to current British or European standards and the product information is correct at the time of going to press.		It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	055Plus
R. Hamilton & Co Ltd. Unit G	Quarry Industrial Estate MER	E. Wiltshire UK BA12 6LA

Tel: +44 (0)1747 860088

Fax: +44 (0)1747 861032

Email: info@hamilton-litestat.com

Web: www.hamilton-litestat.com