

Order Code: 92 FO PB-W

Cheriton Victorian Polished Brass 1 gang 13A Fuse Only. Standard Insert will be Polished Brass with a White surround.

## **Attributes**

Primary Range Cheriton Victorian

Insrt FO
Plate material Metal
Size (single) height 88mm
Size (single) width 88mm
Size (single) depth 8.5mm
Box fixing hole centres 60.3mm

Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT

Grid fixing hole centres details refer to GRID-IT technical pages and GRID-IT catalogue

Minimum wall box depth 35mm Current rating 13 Amp Voltage 220/250V AC Max load 13 Amp IP rating IP2XD Switched Poles none Contact Gap Minimum none Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2

Terminal Capacity 4 1 x 4mm2 Multi-Strand

3 x 2.5mm2

Terminal Capacity 5 1 x 6mm2
Earth Terminal Capacity 1 6 x 1mm2
Earth Terminal Capacity 2 5 x 1.5mm2
Earth Terminal Capacity 3 3 x 2.5mm2

**Terminal Capacity 3** 

BS EN ISO Standard

Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand

Earth Terminal Capacity 5 1 x 6mm2
Product Class 1 Must be earthed
Ambient Operating
Temperature -5° to +40°C
Recommended Location
Max installation Altitude 2000m

Patents And Trademarks Trade Mark No. 2344779

BS 1363-4

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001: 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. NSSPlus DAT





**R. Hamilton & Co Ltd.** Tel: +44 (0)1747 860088

Unit G

Fax: +44 (0)1747 861032

Quarry Industrial Estate

MERE, Wiltshire

UK BA12 6LA

Email: info@hamilton-litestat.com

Web: www.hamilton-litestat.com