

	Order Code : 2 45SS1 PB-W
Cheriton Victor	rian Polished Brass 1 gang
Double Pole	45A Red Rocker + 13A
Switched Sock	ket. Standard Insert will be
Polished Br	ass & Red with a White
	surround.
Attributes	
Primary Range	Cheriton Victorian

Primary Range Insrt 45SS1 Metal Plate material Size (double) height Size (double) width Size (double) depth Box fixing hole centres Minimum wall box depth Current rating Amp Voltage Max load Amp IP rating Switched Poles Contact Gap Minimum 3mm Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 1 x 16mm2 Product Class 1 Ambient Operating Temperature **Recommended Location** Max installation Altitude BS EN ISO Standard Patents And Trademarks Trade Mark No. 2344779

86mm 146mm 8.5mm 120.6mm 35mm Switch 45 Amp Socket 13 220/250V AC Switch 45 Amp Socket 13 IP2XD Double 3 x 6mm2 2 x 10mm2 1 x 16mm2 3 x 6mm2 2 x 10mm2 Must be earthed -5° to +40°C Indoor use only 2000m BS 4177

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.	It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.		
Ilustrations and diagrams are reproduced within the imitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	NSSPlus	Listed in LOCKINS DATABASE	ISO 9001:2008 CERT NO. FM11238

R. Hamilton & Co Ltd. Tel: +44 (0)1747 860088

Unit G Fax: +44 (0)1747 861032 Quarry Industrial Estate MERE, Wiltshire Email: info@hamilton-litestat.com

UK BA12 6LA Web: www.hamilton-litestat.com