• 2. •	
Neutral Live	

Order Code : 94 US2 B Cheriton Victorian Satin Brass 1 gang 2A Unswitched Socket. Standard Insert will be Black.

Attributes

Primary Range Insrt Plate material Size (single) height Size (single) width Size (single) depth Box fixing hole centres Minimum wall box depth Current rating Voltage Max load IP rating Switched Poles **Terminal Capacity 1 Terminal Capacity 2 Terminal Capacity 3 Terminal Capacity 4** Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Ambient Operating Temperature Recommended Location Max installation Altitude BS EN ISO Standard Patents And Trademarks

Cheriton Victorian US2 Metal 88mm 88mm 8.5mm 60.3mm 35mm 2 Amp 220/250V AC 2 Amp IP2XD none 5 x 1mm2 4 x 1.5mm2 2 x 2.5mm2 1 x 4mm2 5 x 1mm2 Must be earthed -5° to +40°C Indoor use only 2000m BS 546 Trade Mark No. 2344779

All products listed conform to current British or European standards and the product information is correct at the time of going to press.		It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	

R. Hamilton & Co Ltd. Tel: +44 (0)1747 860088 Unit G Fax: +44 (0)1747 861032

Quarry Industrial EstateMERE, WiltshireEmail: info@hamilton-litestat.comWe

ire UK BA12 6LA Web: www.hamilton-litestat.com