



Order Code :
84D US5 B
 Sheer Floor Satin Steel 1 gang 5A
 Unswitched Socket. Standard Insert will be
 Black.

Attributes

| | |
|-------------------------------|----------------------------|
| Primary Range | Sheer Floor |
| Insrt | US5 |
| Plate material | Metal |
| Size (single) height | 86mm |
| Size (single) width | 86mm |
| Size (single) depth | 3.0mm (6.5mm Hinged Cover) |
| Box fixing hole centres | 60.3mm |
| Minimum wall box depth | 35mm |
| Current rating | 5 Amp |
| Voltage | 220/250V AC |
| Max load | 5 Amp |
| IP rating | IP2XD |
| Switched Poles | none |
| Terminal Capacity 1 | 5 x 1mm ² |
| Terminal Capacity 2 | 4 x 1.5mm ² |
| Terminal Capacity 3 | 2 x 2.5mm ² |
| Terminal Capacity 4 | 1 x 4mm ² |
| Earth Terminal Capacity 1 | 5 x 1mm ² |
| Earth Terminal Capacity 2 | 4 x 1.5mm ² |
| Earth Terminal Capacity 3 | 2 x 2.5mm ² |
| Earth Terminal Capacity 4 | 1 x 4mm ² |
| Product Class 1 | Must be earthed |
| Ambient Operating Temperature | -5Â° to +40Â°C |
| Recommended Location | Indoor use only |
| Max installation Altitude | 2000m |
| BS EN ISO Standard | BS 546 |

| | | |
|---|---|--|
| <p>All products listed conform to current British or European standards and the product information is correct at the time of going to press.</p> | <p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.</p> | <p>It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p> |
| <p>Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.</p> | <p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.</p> | |

R. Hamilton & Co Ltd. Unit G Quarry Industrial Estate MERE, Wiltshire UK BA12 6LA
 Tel: +44 (0)1747 860088 Fax: +44 (0)1747 861032 Email: info@hamilton-litestat.com Web: www.hamilton-litestat.com