

Order Code: 94 SHS W

Cheriton Victorian Satin Brass Shaver Socket Dual Voltage. Standard Insert will be White.

Attributes

Primary Range Cheriton Victorian

Insrt SHS
Plate material Metal
Size (double) height 146mmV
Size (double) width 86mm
Size (double) depth 8.5mm

Box fixing hole centres 120.6mm Vertical

Minimum wall box depth 47mm Current rating 20VA

Voltage 220/250V AC 200/250V input; 115/230V

Max load 200/250V Inpl

IP ratingIP2XDSwitched PolesnoneContact Gap MinimumnoneTerminal Capacity 15 x 1mm2Terminal Capacity 24 x 1.5mm2Terminal Capacity 33 x 2.5mm2

Terminal Capacity 4 2 x 4mm2 Multi-Strand

Terminal Capacity 5 1×6 mm2 Earth Terminal Capacity 1 9×1 mm2 Earth Terminal Capacity 2 6×1.5 mm2 Earth Terminal Capacity 3 4×2.5 mm2

Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand

Earth Terminal Capacity 5 1 x 6mm2

Product Class 1 Must be earthed

Ambient Operating
Temperature -5° to +40°C

Recommended Location Indoor use only

Max installation Altitude 2000m

BS EN ISO Standard
Additional Notes:

Patents And Trademarks

BS EN 61558 - BS 4573

Must be mounted vertically

Trade Mark No. 2344779

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001: 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. **N55Plus**





R. Hamilton & Co Ltd. Unit G Quarry Industrial Estate MERE, Wiltshire UK BA12 6LA
Tel: +44 (0)1747 860088 Fax: +44 (0)1747 861032 Email: info@hamilton-litestat.com Web: www.hamilton-litestat.com