

Order Code: 92 SS2 PB-W

Cheriton Victorian Polished Brass 2 gang 13A Switched Socket - Double Pole. Standard Insert will be Polished Brass with a White surround.

Attributes

Primary Range Cheriton Victorian

Insrt SS2
Plate material Metal
Size (double) height 86mm
Size (double) width 146mm
Size (double) depth 8.5mm
Box fixing hole centres 120.6mm

Grid fixing inserts are available on Cheriton

Grid fixing hole centres Victorian plates. For full details refer to GRID-IT

technical pages and GRID-IT catalogue

Minimum wall box depth 35mm Current rating 13 Amp Voltage 220/250V AC Max load 13 Amp IP2XD IP rating Switched Poles Double Contact Gap Minimum 3mm Terminal Capacity 1 4 x 2.5mm2

Terminal Capacity 2 3 x 4mm2

Terminal Capacity 3 2 x 6mm2 Multi-Strand

Terminal Capacity 4 1 x 10mm2 Earth Terminal Capacity 1 4 x 2.5mm2 Earth Terminal Capacity 2 3 x 4mm2

Earth Terminal Capacity 3 2 x 6mm2 Multi-Strand

Earth Terminal Capacity 4 1 x 10mm2
Product Class 1 Must be earthed
Ambient Operating
Temperature -5° to +40°C
Recommended Location Indoor use only
Max installation Altitude 2000m

BS EN ISO Standard BS 1363-2

Patents And Trademarks Trade Mark No. 2344779

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. NSSPlus LUCK





R. Hamilton & Co Ltd.

Unit G

Quarry Industrial Estate

MERE, Wiltshire

UK BA12 6LA

Tel: +44 (0)1747 860088

Fax: +44 (0)1747 861032

Email: info@hamilton-litestat.com

Web: www.hamilton-litestat.com