



Hamilton® CHERITON GEORGIAN
1 GANG 13A FUSE
ONLY + CABLE OUTLET



Order Code :
91 FOC AB-B

Cheriton Georgian Antique Brass 1 gang 13A Fuse + Cable Outlet. Standard Insert will be Antique Brass with a Black surround.

Attributes

| | |
|-------------------------------|--|
| Primary Range | Cheriton Georgian |
| Insrt | FOC |
| Plate material | Metal |
| Size (single) height | 88mm |
| Size (single) width | 88mm |
| Size (single) depth | 10.8mm |
| Box fixing hole centres | 60.3mm |
| Grid fixing hole centres | Grid fixing inserts are available on Cheriton Georgian plates. For full details refer to GRID-IT technical pages and GRID-IT catalogue |
| Minimum wall box depth | 35mm |
| Current rating | 13 Amp |
| Voltage | 220/250V AC |
| Max load | 13 Amp |
| IP rating | IP2XD |
| Switched Poles | none |
| Contact Gap Minimum | none |
| Terminal Capacity 1 | 5 x 1mm ² |
| Terminal Capacity 2 | 4 x 1.5mm ² |
| Terminal Capacity 3 | 3 x 2.5mm ² |
| Terminal Capacity 4 | 1 x 4mm ² Multi-Strand |
| Terminal Capacity 5 | 1 x 6mm ² |
| Earth Terminal Capacity 1 | 6 x 1mm ² |
| Earth Terminal Capacity 2 | 5 x 1.5mm ² |
| Earth Terminal Capacity 3 | 3 x 2.5mm ² |
| Earth Terminal Capacity 4 | 2 x 4mm ² Multi-Strand |
| Earth Terminal Capacity 5 | 1 x 6mm ² |
| Product Class 1 | Must be earthed |
| Ambient Operating Temperature | -5Â° to +40Â°C |
| Recommended Location | Indoor use only |
| Max installation Altitude | 2000m |
| BS EN ISO Standard | BS 1363-4 |
| Cable outlet (min) | 0.75mm ² |
| Cable outlet (max) | 2.5mm ² |
| Patents And Trademarks | Trade Mark No. 2344779 |

| | | |
|--|--|---|
| All products listed conform to current British or European standards and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System. | It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. | |

R. Hamilton & Co Ltd. Unit G Quarry Industrial Estate MERE, Wiltshire UK BA12 6LA
 Tel: +44 (0)1747 860088 Fax: +44 (0)1747 861032 Email: info@hamilton-litestat.com Web: www.hamilton-litestat.com