	Cheritor Unswitc Attributes
	Primary Ra Insrt Plate mate Size (singl Size (singl Box fixing Minimum v Current rat Voltage Max load IP rating Switched F Terminal C Terminal C
Neutral Earth Live	Terminal C Earth Term Earth Tern Earth Tern Earth Tern Product Cl Ambient O Temperatu Recomme Max install BS EN ISC

Order Code : 91 US2 B n Georgian Antique Brass 1 gang 2A ched Socket. Standard Insert will be Black.

## s

ange erial e) height e) width e) depth hole centres vall box depth ting Poles Capacity 1 apacity 2 Capacity 3 Capacity 4 ninal Capacity 1 5 x 1mm2 ninal Capacity 2 4 x 1.5mm2 ninal Capacity 3 2 x 2.5mm2 ninal Capacity 4 1 x 4mm2 ass 1 perating ire nded Location lation Altitude ) Standard Patents And Trademarks

Cheriton Georgian US2 Metal 88mm 88mm 10.8mm 60.3mm 35mm 2 Amp 220/250V AC 2 Amp IP2XD none 5 x 1mm2 4 x 1.5mm2 2 x 2.5mm2 1 x 4mm2 Must be earthed -5° to +40°C Indoor use only 2000m BS 546 Trade Mark No. 2344779

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.	It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	NSSPlus

R. Hamilton & Co Ltd. Tel: +44 (0)1747 860088 Unit G Fax: +44 (0)1747 861032

MERE, Wiltshire Quarry Industrial Estate Email: info@hamilton-litestat.com

UK BA12 6LA Web: www.hamilton-litestat.com