

Order Code: 74 SPN SS-W

Hartland Satin Steel 1 gang 13A Fused Spur, Double Pole + Neon. Standard Insert will be Satin Steel with a White surround.

Attributes

Primary Range Hartland SPN Insrt Plate material Metal Size (single) height 88mm Size (single) width 88mm Size (single) depth 5mm Box fixing hole centres 60.3mm

> Grid fixing inserts are available on Hartland

plates. For full details refer Grid fixing hole centres to GRID-IT technical pages

and GRID-IT catalogue.

Minimum wall box depth 35mm Current rating 13 Amp Voltage 220/250V AC Max load 13 Amp IP rating IP2XD Switched Poles Double Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2

Terminal Capacity 2 2 x 4mm2 Multi-Strand

Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2

Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand

Earth Terminal Capacity 5 1 x 6mm2 Product Class 1 Must be earthed **Ambient Operating** -5° to +40°C Temperature Recommended Location Indoor use only Max installation Altitude 2000m BS EN ISO Standard BS 1363-4

Trade Mark No. 2344778 Patents And Trademarks

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001: 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. กรรPlus



R. Hamilton & Co Ltd. Unit G Quarry Industrial Estate

MERE, Wiltshire

UK BA12 6LA Tel: +44 (0)1747 860088 Fax: +44 (0)1747 861032 Email: info@hamilton-litestat.com Web: www.hamilton-litestat.com