




NO IMAGE
AVAILABLE

Order Code :
I DKIT SB
G/Fix Dimmer Kit inc Knob and Inlays Satin
Brass. Standard Insert will be Satin Brass.

Attributes

| | |
|-------------------------------|---------------------------------------|
| Insert type | Dimmer Kit containing knob and inlays |
| Box fixing hole centres | n/a |
| Minimum wall box depth | n/a |
| Current rating | n/a |
| Voltage | n/a |
| Max load | n/a |
| Mains Frequency | n/a |
| IP rating | IP2XD |
| Switched Poles | n/a |
| Contact Gap Minimum | n/a |
| Product Class 1 | Face plate must be earthed |
| Ambient Operating Temperature | -5° to +40°C |
| Recommended Location | indoor use only |
| Max installation Altitude | 2000m |

| | | |
|--|--|---|
| All products listed conform to current British or European standards and the product information is correct at the time of going to press. | All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System. | It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. |
| Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding. | Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. |    |

R. Hamilton & Co Ltd. Unit G Quarry Industrial Estate MERE, Wiltshire UK BA12 6LA
 Tel: +44 (0)1747 860088 Fax: +44 (0)1747 861032 Email: info@hamilton-litestat.com Web: www.hamilton-litestat.com