

Order Code: IDTS SS-W

Grid Fix Module Multi way Touch Slave Trailing Edge Satin Steel/White. Standard Insert will be Satin Steel with a White surround.

Attributes

Voltage

Primary Range **GRID-IT** Secondary Range **Grid Fix Inserts**

DTS Minimum wall box depth 35mm

The same as Touch Master Wattage

or Ceiling Dimmer

The same as Touch Master Current rating

or Ceiling Dimmer 220/250V AC

The same as Touch Master Max load

or Ceiling Dimmer

IP rating Terminal Capacity 1 2 x 1mm2 Terminal Capacity 2 2 x 1.5mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2

Earth Terminal Capacity 4 1 x 4mm2 Multi-Strand

Earth Terminal Capacity 5 1 x 6mm2

Face plate must be earthed Product Class 1

Ambient Operating

Additional Notes:

-5° to +40°C Temperature

Indoor use only Recommended Location Max installation Altitude 2000m

BS EN ISO Standard BS EN 60669-2-1

> Tungsten filament GU10 lamps must be branded with a fuse base. When

using mains

voltagehalogen lampsdimmers should be de-rated by 25%. When using mains voltage

halogen load transformer maximum rating is 210VA. To only be used with Touch

Master Dimmers

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001: 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. กรรPlus





R. Hamilton & Co Ltd.

Unit G

Quarry Industrial Estate

MERE, Wiltshire

UK BA12 6LA

Tel: +44 (0)1747 860088

Fax: +44 (0)1747 861032

Email: info@hamilton-litestat.com

Web: www.hamilton-litestat.com