






2 Way and Intermediate Switching Wiring Methods







Order Code: 94 R21 SB-B

Cheriton Victorian Satin Brass 1 gang 2 Way 10AX Rocker. Standard Insert will be Satin Brass with a Black surround.

Attributes

Primary Range Cheriton Victorian

Insrt R21
Plate material Metal
Size (single) height 88mm
Size (single) width 88mm
Size (single) depth 8.5mm
Box fixing hole centres 60.3mm

Grid fixing inserts are available on Cheriton Victorian plates. For full details refer to GRID-IT

Grid fixing hole centres details refer to GRID-IT technical pages and GRID-IT catalogue

Minimum wall box depth 25mm
Current rating 10AX
Voltage 220/250V AC
Max load 10 Amp inductive

IP rating IP2XD
Switched Poles Single
Contact Gap Minimum 3mm
Terminal Capacity 1 5 x 1mm2
Terminal Capacity 2 4 x 1.5mm2
Terminal Capacity 3 1 x 2.5mm2

Terminal Capacity 4 1 x 4mm2 Multi-Strand

Terminal Capacity 5 1 x 6mm2
Earth Terminal Capacity 1 5 x 1mm2
Earth Terminal Capacity 2 4 x 1.5mm2
Earth Terminal Capacity 3 3 x 2.5mm2

Earth Terminal Capacity 4 1 x 4mm2 Multi-Strand

Earth Terminal Capacity 5 1 x 6mm2
Product Class 1 Must be earthed
Ambient Operating
Temperature -5° to +40°C
Recommended Location Indoor use only
Max installation Altitude 2000m

BS EN ISO Standard BS EN 60669-1

Patents And Trademarks Trade Mark No. 2344779

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. **N5SPlus**





R. Hamilton & Co Ltd.

Unit G

Quarry Industrial Estate

MERE, Wiltshire

UK BA12 6LA

Tel: +44 (0)1747 860088

Fax: +44 (0)1747 861032

Email: info@hamilton-litestat.com

Web: www.hamilton-litestat.com