



Order Code: 84 SP SS-W

Sheer Satin Steel 1 gang 13A Fused Spur, Double Pole. Standard Insert will be Satin Steel with a White surround.

Attributes

Primary Range Sheer
Insrt SP
Plate material Metal
Size (single) height 86mm
Size (single) width 86mm
Size (single) depth 1.5mm
Box fixing hole centres 60.3mm

Grid fixing inserts are available on Sheer plates.

Grid fixing hole centres For full details refer to GRID-IT technical pages

and GRID-IT catalogue

Minimum wall box depth 35mm Current rating 13 Amp Voltage 220/250V AC Max load 13 Amp IP rating IP2XD Switched Poles Double Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2

Terminal Capacity 2 2 x 4mm2 Multi-Strand

Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2

Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand

Earth Terminal Capacity 5
Product Class 1
Ambient Operating
Temperature
Recommended Location
Max installation Altitude
BS EN ISO Standard

1 x 6mm2
Must be earthed
-5° to +40°C
Indoor use only
2000m
BS 1363-4

Patents And Trademarks Trade Mark No. 2296586

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. กรรPlus





R. Hamilton & Co Ltd. Unit G Quarry Industrial Estate MERE, Wiltshire Tel: +44 (0)1747 860088 Fax: +44 (0)1747 861032 Email: info@hamilton-litestat.com Web:

Web: www.hamilton-litestat.com

UK BA12 6LA