



Order Code :  
 84D US99 B  
 Sheer Floor Satin Steel 2 gang 13A  
 Unswitched Socket. Standard Insert will be  
 Black.

**Attributes**

|                               |                                   |
|-------------------------------|-----------------------------------|
| Primary Range                 | Sheer Floor                       |
| Insrt                         | US99                              |
| Plate material                | Metal                             |
| Size (double) height          | 94mm                              |
| Size (double) width           | 144mm                             |
| Size (double) depth           | 3.0mm (6.5mm Hinged Cover)        |
| Box fixing hole centres       | 120.6mm                           |
| Minimum wall box depth        | 35mm                              |
| Current rating                | 13 Amp                            |
| Voltage                       | 220/250V AC                       |
| Max load                      | 13 Amp                            |
| IP rating                     | IP2XD                             |
| Switched Poles                | none                              |
| Terminal Capacity 1           | 5 x 2.5mm <sup>2</sup>            |
| Terminal Capacity 2           | 3 x 4mm <sup>2</sup>              |
| Terminal Capacity 3           | 2 x 6mm <sup>2</sup> Multi-Strand |
| Terminal Capacity 4           | 1 x 10mm <sup>2</sup>             |
| Earth Terminal Capacity 1     | 5 x 2.5mm <sup>2</sup>            |
| Earth Terminal Capacity 2     | 3 x 4mm <sup>2</sup>              |
| Earth Terminal Capacity 3     | 2 x 6mm <sup>2</sup> Multi-Strand |
| Earth Terminal Capacity 4     | 1 x 10mm <sup>2</sup>             |
| Product Class 1               | Must be earthed                   |
| Ambient Operating Temperature | -5Â° to +40Â°C                    |
| Recommended Location          | Indoor use only                   |
| Max installation Altitude     | 2000m                             |
| BS EN ISO Standard            | BS 1363-2                         |

|   |   |  |
|---|---|--|
| <p>All products listed conform to current British or European standards and the product information is correct at the time of going to press.</p> | <p>All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.</p>                 | <p>It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.</p> |
| <p>Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.</p>                  | <p>Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.</p> |  |

**R. Hamilton & Co Ltd.**      Unit G      Quarry Industrial Estate      MERE, Wiltshire      UK BA12 6LA  
 Tel: +44 (0)1747 860088      Fax: +44 (0)1747 861032      Email: info@hamilton-litestat.com      Web: www.hamilton-litestat.com