•	
Screen Under Cable Clamp	Each coaxial cable should be connected to the appropriate terminal as shown. This diagram applies to all unscreened non-isolated and isolated connections including diplex (TV/FM) units. Care should be taken to ensure that the screening braid is clamped securely by the cable clamp and does not come into contact with the centre conductor.

## Order Code : 94 TV2 B Cheriton Victorian Satin Brass 2 gang Non Isolated Television 2in/2out. Standard Insert will be Black.

## Attributes

Primary Range Insrt Plate material Size (single) height Size (single) width Size (single) depth Box fixing hole centres Minimum wall box depth IP rating Earth Terminal Capacity 1 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Multi-Strand Earth Terminal Capacity 5

Product Class 1

Ambient Operating Temperature Recommended Location Max installation Altitude Patents And Trademarks

TV2 Metal 88mm 88mm 8.5mm 60.3mm 25mm IP2XD 5 x 1mm2 1 x 6mm2 Must be earthed (ref BS7671 415.2.1)

Cheriton Victorian

-5° to +40°C

Indoor use only 2000m Trade Mark No. 2344779

All products listed conform to current British or European standards and the product information is correct at the time of going to press.	All accessories are manufactured under an accredited	It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.
Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.	Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.	NSSPlus

R. Hamilton & Co Ltd. Tel: +44 (0)1747 860088

Unit G Fax: +44 (0)1747 861032

MERE, Wiltshire **Quarry Industrial Estate** Email: info@hamilton-litestat.com

UK BA12 6LA Web: www.hamilton-litestat.com