

## Order Code: 74 SP SS-B

Hartland Satin Steel 1 gang 13A Fused Spur, Double Pole. Standard Insert will be Satin Steel with a Black surround.

## **Attributes**

Primary Range Hartland
Insrt SP
Plate material Metal
Size (single) height 88mm
Size (single) width 88mm
Size (single) depth 5mm
Box fixing hole centres 60.3mm

Grid fixing inserts are available on Hartland

Grid fixing hole centres plates. For full details refer to GRID-IT technical pages

and GRID-IT catalogue.

Minimum wall box depth 35mm Current rating 13 Amp Voltage 220/250V AC Max load 13 Amp IP rating IP2XD Switched Poles Double Contact Gap Minimum 3mm Terminal Capacity 1 3 x 2.5mm2

Terminal Capacity 2 2 x 4mm2 Multi-Strand

Terminal Capacity 3 1 x 6mm2
Earth Terminal Capacity 1 6 x 1mm2
Earth Terminal Capacity 2 5 x 1.5mm2
Earth Terminal Capacity 3 3 x 2.5mm2

Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand

Earth Terminal Capacity 5
Product Class 1
Ambient Operating
Temperature
Recommended Location
Max installation Altitude
BS EN ISO Standard

1 x 6mm2
Must be earthed
-5° to +40°C
Indoor use only
2000m
BS 1363-4

Patents And Trademarks Trade Mark No. 2344778

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001 : 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. ∩**5**5Plus





**R. Hamilton & Co Ltd.** Tel: +44 (0)1747 860088

Unit G

Fax: +44 (0)1747 861032 Em

Quarry Industrial Estate

MERE, Wiltshire

UK BA12 6LA

Email: info@hamilton-litestat.com

Web: www.hamilton-litestat.com