





## Order Code: 92 US5 W

Cheriton Victorian Polished Brass 1 gang 5A Unswitched Socket. Standard Insert will be White.

## **Attributes**

Primary Range Cheriton Victorian

Insrt US<sub>5</sub> Plate material Metal Size (single) height 88mm Size (single) width 88mm Size (single) depth 8.5mm Box fixing hole centres 60.3mm Minimum wall box depth 35mm Current rating 5 Amp Voltage 220/250V AC Max load 5 Amp

IP rating IP2XD Switched Poles none Terminal Capacity 1 5 x 1mm2 Terminal Capacity 2 4 x 1.5mm2 Terminal Capacity 3 2 x 2.5mm2 Terminal Capacity 4 1 x 4mm2 Earth Terminal Capacity 1 5 x 1mm2 Earth Terminal Capacity 2 4 x 1.5mm2 Earth Terminal Capacity 3 2 x 2.5mm2 Earth Terminal Capacity 4 1 x 4mm2 Product Class 1 Must be earthed Ambient Operating -5° to +40°C Temperature

Max installation Altitude 2000m BS EN ISO Standard BS 546

Recommended Location

Patents And Trademarks Trade Mark No. 2344779

Indoor use only

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001: 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes.

กรรPlus





R. Hamilton & Co Ltd. Unit G Quarry Industrial Estate Tel: +44 (0)1747 860088 Fax: +44 (0)1747 861032 Email: info@hamilton-litestat.com

MERE, Wiltshire Web: www.hamilton-litestat.com

UK BA12 6LA