

Order Code: 92 SPNC PB-B

Cheriton Victorian Polished Brass 1 gang 13A Fused Spur, Double Pole + Neon + Cable Outlet, Standard Insert will be Polished Brass with a Black surround.

Attributes

Primary Range Cheriton Victorian

Insrt SPNC Plate material Metal Size (single) height 88mm Size (single) width 88mm Size (single) depth 8.5mm Box fixing hole centres 60.3mm

Grid fixing inserts are available on Cheriton Victorian plates. For full

Grid fixing hole centres details refer to GRID-IT

technical pages and GRID-IT catalogue

Minimum wall box depth 35mm Current rating 13 Amp Voltage 220/250V AC Max load 13 Amp IP rating IP2XD Switched Poles Double Contact Gap Minimum 3mm

Terminal Capacity 1 3 x 2.5mm2

Terminal Capacity 2 2 x 4mm2 Multi-Strand

Terminal Capacity 3 1 x 6mm2 Earth Terminal Capacity 1 6 x 1mm2 Earth Terminal Capacity 2 5 x 1.5mm2 Earth Terminal Capacity 3 3 x 2.5mm2

Earth Terminal Capacity 4 2 x 4mm2 Multi-Strand

Earth Terminal Capacity 5 1 x 6mm2 **Product Class 1** Must be earthed **Ambient Operating** -5° to +40°C Temperature Recommended Location Indoor use only

Max installation Altitude 2000m BS EN ISO Standard BS 1363-4 Cable outlet (min) 0.75mm \hat{A}^2 Cable outlet (max) 2.5mmÂ²

Patents And Trademarks Trade Mark No. 2344779

All products listed conform to current British or European standards and the product information is correct at the time of going to press.

All accessories are manufactured under an accredited BS EN ISO 9001: 2008 Quality System.

It is the policy of the company to continually improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice.

Illustrations and diagrams are reproduced within the limitations of reproductions and printing processes are not binding.

Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. กรรPlus





R. Hamilton & Co Ltd.

Unit G

Quarry Industrial Estate

MERE, Wiltshire

UK BA12 6LA

Tel: +44 (0)1747 860088

Fax: +44 (0)1747 861032

Email: info@hamilton-litestat.com

Web: www.hamilton-litestat.com