



- Fixed Thermal & Magnetic Elements
- 25kA @ 240V AC to BS EN 60947-2
- Fitted with box terminals on line and load sides
- For use in Powerstar 250 outgoing Ways only

Product Specification Data		Revision Date: 15/10/2021
Rated permanent current Iu	20 A	
Rated voltage	240 V	
Rated short-circuit breaking capacity Icu at 400 V, 50 Hz	25 kA	
Integrated earth fault protection	No	
Type of electrical connection of main circuit	Other	
Device construction	Complete device in housing	
Suitable for DIN rail (top hat rail) mounting	No	
DIN rail (top hat rail) mounting optional	No	
Number of auxiliary contacts as normally closed contact	0	
Number of auxiliary contacts as normally open contact	0	
Number of auxiliary contacts as change-over contact	0	
With switched-off indicator	No	
With under voltage release	No	
Number of poles	1	
Position of connection for main current circuit	Other	
Type of control element	Toggle	
Complete device with protection unit	Yes	
Motor drive integrated	No	
Motor drive optional	No	
Terminal Capacity L&N	16 mm ²	
Frequency	50/60 Hz	
CE Conformity	Yes	
WEEE Symbol	Yes	
UKCA Conformity	Yes	
Height	121 mm	
Width	25 mm	
Depth	88 mm	
Weight	0 Kg	
Country Of Origin	Mexico	

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.



Electrium Sales Limited, Walkmill Lane, Cannock WS11 0XE
01543 455000 www.electrium.co.uk info@electrium.co.uk