



## List No. NHSW363 NH FUSE COMBINATION UNITS

63A 3P+N Enclosed Switch Disconnecter - Size 1



- Enclosed switch disconnecter
- Painted RAL 7035 steel enclosure with hinged door. 220mmH x 157.5mmW x 133.5mmD

### Product Specification Data

Revision Date: 15/10/2021

|  |                            |
|--|----------------------------|
| Version as main switch                 | No                         |
| Version as safety switch               | No                         |
| Max. rated operation voltage Ue AC     | 415 V                      |
| Rated permanent current Iu             | 63 A                       |
| Number of poles                        | 3                          |
| Cable entry                            | Other                      |
| Equipped with connectors               | Yes                        |
| Suitable for ground mounting           | No                         |
| Suitable for front mounting 4-hole     | No                         |
| Suitable for busbar mounting           | No                         |
| Type of control element                | Door coupling rotary drive |
| Position control element               | Front side                 |
| Motor drive optional                   | No                         |
| Motor drive integrated                 | No                         |
| Version as emergency stop installation | No                         |
| Terminal Capacity L&N                  | 25 mm <sup>2</sup>         |
| Frequency                              | 50-60 Hz                   |
| CE Conformity                          | Yes                        |
| WEEE Symbol                            | Yes                        |
| UKCA Conformity                        | Yes                        |

Although every effort has been made to ensure accuracy in the compilation of the technical detail within this datasheet, specifications and performance data are constantly changing. Latest details can be obtained from the Electrium website.