

## TKE/B 40



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

<b>Material cable gland</b>	Brass nickel-plated
<b>Material sealing gasket</b>	EPDM
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP69, IP68 (5 bar 30 min)
<b>Surface</b>	Nickel-plated
<b>Thread type</b>	M
<b>Ø Connection thread D</b>	40
<b>Lead</b>	1,5
<b>Length screw-in thread L</b>	8 mm
<b>Key width SW</b>	46 mm
<b>Total length TL</b>	44 mm - 55 mm
<b>Type of cable anchorage</b>	A
<b>Install. torques fitting</b>	20 N/m
<b>Install. torques cap nut</b>	20 N/m
<b>Impact category</b>	6
<b>Order no. nickel-plated</b>	10106234
<b>Type</b>	TKE/B 40
<b>Packing unit</b>	1
<b>ETIM-Classification</b>	EC000441

Description:

IP 68 Brass cable gland. EMSKV 40/ MFD 2 x 11 mm Tails and 1 x 6 mm Earth. Kit contains insert, locknut and blanking insert.

13.10.2020

Your Contact:

**WISKA UK Ltd.**

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk