

CW 32 Pack

Cable gland pack british standard BS 6121



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

| | |
|-----------------------------------|------------|
| Material | Brass |
| Material shrouds | PVC |
| Temp. range min | -20 °C |
| Temp. range max | 80 °C |
| Protection class | IP66 |
| Thread type | M |
| Ø Connection thread D | 32 |
| Lead | 1,5 |
| Length screw-in thread L | 10 mm |
| Ø cable diameter min | 26 mm |
| Ø cable diameter max | 33,5 mm |
| Ø cable below cable shield | -26,5 mm |
| Key width SW | 43 mm |
| Collar diameter (E) | 50 mm |
| Total length TL | 58 mm |
| Surface | Bright |
| Order no. bright | 50101676 |
| Type | CW 32 Pack |
| Packing unit | 2 |

13.10.2020

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk



Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk