

TKE/P 32/FFD/10-16



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

Material cable gland	Polyamide
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP66
Product Color	RAL 7035
Thread type	M
Ø Connection thread D	32
Lead	1,5
Length screw-in thread L	12 mm
Key width SW	36 mm
Total length TL	42 mm - 51 mm
Glow wire test	750 °C
Type of cable anchorage	A
Install. torques fitting	15 N/m
Install. torques cap nut	4 N/m
Impact category	4
Order no. RAL 7035	10106243
Type	TKE/P 32/FFD/10-16
Packing unit	1
ETIM-Classification	EC000441

Description:

IP 68 Plastic cable gland for flat cable insert. ESKV 32/ FFD for 1 x 10-16 mm twin and earth. Kit contains insert, and locknut.

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708



info@wiska.co.uk · www.wiska.co.uk

13.10.2020

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk