

## SHARK 6803 AW

### SHARK SIXEIGHT



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

<b>Material</b>	Polyamide
<b>Filling</b>	Silicone
<b>Temp. range min</b>	-20 °C
<b>Temp. range max</b>	90 °C
<b>Glow wire test</b>	self-extinguishing
<b>Protection class</b>	IP68
<b>Voltage</b>	0,6 kV - 1 kV
<b>Order no. UK</b>	SH6803AW
<b>Type</b>	SHARK 6803 AW
<b>Packing unit</b>	1
<b>ETIM-Classification</b>	EC001169

#### Remarks:

Ampere: 135  
 Cable Size: (5 core) 10 - 25 mm  
 LxBxH: 310x85x60 mm

#### Description:

SHARK SIXEIGHT IP 68 rated pre-filled gel insulated joint, including modular bolts and gaskets, cable retention clamp, spring coil and earthing braid.

#### Additional Info:

Ready to use, re-enterable, 100% watertight, 100% dust-tight, suitable for SWA cables, no mixing or pouring, immediate operation, excellent electrical insulation, good mechanical strength, no expiry date.

#### Your Contact:

##### WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708



info@wiska.co.uk · www.wiska.co.uk

13.10.2020

Your Contact:

**WISKA UK Ltd.**

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk