Xnightsbridge

DATASHEET



FPR7000BC

Flat plate 13A 1G DP switched socket - brushed chrome with black insert

www.mlaccessories.co.uk

| INST WEIGHT (KG) INSERT COLOUR INS | MLA PART CODE | FPR7000BC |
|--|--|------------------------------------|
| Brushed Chrome Black Height - 87.5 Width - 87.5 Projection - 2.5 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION PRATING NPUT VOLTAGE SWITCH TYPE Double Pole EARTH TERMINAL COAD/MAX. LOAD TERMINAL CAPACITY VARRANTY Brushed Chrome Black Height - 87.5 Width - 87.5 Projection - 2.5 Double Pole 120 130 130 130 130 130 130 130 | DESCRIPTION | |
| NSERT COLOUR Black Height - 87.5 Width - 87.5 Projection - 2.5 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION CONSTRUCTION PRATING IP20 NPUT VOLTAGE SWITCH TYPE Double Pole EARTH TERMINAL Yes COAD/MAX. LOAD 13A FERMINAL CAPACITY SVARRANTY 25year(s) | NET WEIGHT (KG) | 0.1105 |
| Height - 87.5 Width - 87.5 Projection - 2.5 MINIMUM MOUNTING BOX DEPTH CONSTRUCTION CONSTRUCTION CONSTRUCTION PRATING IP20 NPUT VOLTAGE SWITCH TYPE Double Pole EARTH TERMINAL COAD/MAX. LOAD TERMINAL CAPACITY YARRANTY Height - 87.5 Width - 87.5 Projection - 2.5 Construction - Premium grade steel IP20 Double Premium grade steel IP20 1P20 1P20 230V 50Hz Double Pole 3 x 2.5mm² or 2 x 4.0mm² 25year(s) | FINISH | Brushed Chrome |
| MINIMUM MOUNTING BOX DEPTH 25mm CONSTRUCTION CONSTRUCTION PRATING NPUT VOLTAGE SWITCH TYPE EARTH TERMINAL COAD/MAX. LOAD TERMINAL CAPACITY VARRANTY Width - 87.5 Projection - 2.5 Projection - 2.5 Construction - Premium grade steel IP20 IP20 Double Pole 230V 50Hz Double Pole 13A 3 x 2.5mm² or 2 x 4.0mm² 25year(s) | INSERT COLOUR | Black |
| CONSTRUCTION Construction - Premium grade steel P RATING IP20 NPUT VOLTAGE 230V 50Hz SWITCH TYPE Double Pole EARTH TERMINAL Yes .OAD/MAX. LOAD 13A TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² VARRANTY 25year(s) | DIMENSIONS (MM) | Width - 87.5 |
| P RATING NPUT VOLTAGE SWITCH TYPE Double Pole EARTH TERMINAL OAD/MAX. LOAD TERMINAL CAPACITY VARRANTY PRATING 1P20 230V 50Hz Double Pole Yes 3 x 2.5mm² or 2 x 4.0mm² 25year(s) | MINIMUM MOUNTING BOX DEPTH | 25mm |
| NPUT VOLTAGE 230V 50Hz SWITCH TYPE Double Pole EARTH TERMINAL Yes .OAD/MAX. LOAD 13A TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² VARRANTY 25year(s) | CONSTRUCTION | Construction - Premium grade steel |
| SWITCH TYPE Double Pole EARTH TERMINAL Yes .OAD/MAX. LOAD 13A TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² VARRANTY 25year(s) | IP RATING | IP20 |
| EARTH TERMINAL Yes .OAD/MAX. LOAD 13A TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² VARRANTY 25year(s) | INPUT VOLTAGE | 230V 50Hz |
| .OAD/MAX. LOAD 13A TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² VARRANTY 25year(s) | SWITCH TYPE | Double Pole |
| TERMINAL CAPACITY 3 x 2.5mm² or 2 x 4.0mm² VARRANTY 25year(s) | EARTH TERMINAL | Yes |
| VARRANTY 25year(s) | LOAD/MAX. LOAD | 13A |
| , , , | TERMINAL CAPACITY | 3 x 2.5mm² or 2 x 4.0mm² |
| MANUFACTURED IN ACCORDANCE WITH BS 1363-2 | WARRANTY | 25year(s) |
| | MANUFACTURED IN ACCORDANCE WITH | BS 1363-2 |
| DRIGIN OF MANUFACTURE China | ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) Yes | DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN 5055832957362 | EAN | 5055832957362 |

Date Created: 01/03/2023 11:24





