

Metal Cable Cleats



- Oval mounting slot for varying cable thicknesses

Part Number	Description	Min Cable Dia. (mm)	Max Cable Dia. (mm)	Width (mm)	Fixing Diameter (mm)	Pack Qty
QC3MBK	Metal Cable Cleats 5.0-7.6mm	5	7.6	16.3	5.7	10
QC4MBK	Metal Cable Cleats 7.7-10.0mm	7.7	10	16.3	5.7	10
QC5MBK	Metal Cable Cleats 10.1-12.7mm	10.1	12.7	16.5	5.7	10
QC6MBK	Metal Cable Cleats 12.6-15.2mm	12.6	15.2	16.5	5.7	10
QC7MBK	Metal Cable Cleats 15.1-17.8mm	15.1	17.8	16.5	5.7	10
QC8MBK	Metal Cable Cleats 17.7-20.3mm	17.7	20.3	20.3	5.7	10
QC9MBK	Metal Cable Cleats 20.2-22.8mm	20.2	22.8	20.5	5.7	10
QC10MBK	Metal Cable Cleats 22.7-25.4mm	22.7	25.4	20.3	5.7	10
QC11MBK	Metal Cable Cleats 25.3-27.7mm	25.3	27.7	22.5	5.7	10
QC12MBK	Metal Cable Cleats 27.6-30.5mm	27.6	30.5	25.3	5.7	10
QC14MBK	Metal Cable Cleats 30.4-35.5mm	30.4	35.5	25.3	5.7	10
QC16MBK	Metal Cable Cleats 35.4-40.6mm	35.4	40.6	25.3	5.7	10
QC18MBK	Metal Cable Cleats 40.5-45.7mm	40.5	45.7	25.3	5.7	10
QC20MBK	Metal Cable Cleats 45.6-50.8mm	45.6	50.8	25.3	5.7	10

Stainless Steel Roller Ball Cable Ties



- Made from 316 grade steel
- Minimum loop tensile strength 4.6mm wide = 44kg
- Minimum loop tensile strength 7.9mm wide = 110kg



Part Number	Finish	Length (mm)	Width (mm)	Bundle Diameter (mm)	Min. Tensile Strength (Kg)	Pack Qty
QSST150S	Steel	150	4.6	35	44	100
QSST200S	Steel	200	4.6	50	44	100
QSST300S	Steel	300	4.6	83	44	100
QSST300LH	Steel	300	7.9	83	110	100
QSST360LH	Steel	360	7.9	100	110	100
QSST360S	Steel	360	4.6	100	44	100
QSST520S	Steel	520	4.6	150	44	100
QSST520LH	Steel	520	7.9	150	110	50
QSST840LH	Steel	840	7.9	250	110	50