

Ring



Part Number	Stud Size (mm)	Pack Qty
QBR3	3	100
QBR37	3.7	100
QBR4	4	100
QBR5	5	100
QBR6	6	100
QBR8	8	100
QBR10	10	100
QBR12	12	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)

Male Push-on



Part Number	Tab Size (mm)	Pack Qty
QBPO48M5	4.8 x 0.5	100
QBPO48M8	4.8 x 0.8	100
QBPO63M	6.3 x 0.8	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)

Female Push-on



Part Number	Tab Size (mm)	Pack Qty
QBPO48F5	4.8 x 0.5	100
QBPO48F8	4.8 x 0.8	100
QBPO63F	6.3 x 0.8	100
QBPO85F	8.5 x 0.8	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)

Spade



Part Number	Stud Size (mm)	Pack Qty
QBF3	3	100
QBF3N	3.5	100
QBF4N	4	100
QBF5	5	100
QBF6	6	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)

Female Push-on Fully Insulated



Part Number	Tab Size (mm)	Pack Qty
QBFPO48F5	4.8 x 0.5	100
QBFPO48F8	4.8 x 0.8	100
QBFPO63F	6.3 x 0.8	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)

Blade



Part Number	Dia x Length (mm)	Pack Qty
QBBL9	2.8 x 9	100
QBBL18	2.2 x 18	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)

Butt



Part Number	Pack Qty
QBB	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)

Piggy Back Push-on Connector



Part Number	Tab Size (mm)	Pack Qty
QBPOA63	6.3 x 0.8	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)


Pin



Part Number	Dia x Length (mm)	Pack Qty
QBP12	1.9 x 12	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)

Heat Shrink Butt



Part Number	Pack Qty
QHSHB2	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)

Male Bullet



Part Number	Bullet Dia (mm)	Pack Qty
QBAB4M	4	100
QBAB5M	5	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)

Female Bullet



Part Number	Bullet Dia (mm)	Pack Qty
QBAB4F	4	100
QBAB5F	5	100

Cable Size Range (mm): 1.5 to 2.5
Current Rating (A): (Max) Voltage (A): (Max)