

### Switch Disconnect Incomer

**Characteristics:**

- Metal switch disconnect incomer consumer units, single row from 10 to 20 outgoing ways.
- All consumer units contain rear cable entry, along with top & bottom knockouts.
- Supplied with a full metal DIN rail, 100A switch disconnect incomer and a full complement of earth and neutral terminals along with marking labels, busbar, instructions, rear cable protector plate and meter tail clamp.
- Recommended for use with TT systems when utilising RCBO on outgoing circuits.
- Conforms to BS EN 61439-3 including Annex ZB (16kA rating).
- Adjustable depth in wall 72mm-92mm.
- For dimensions see page 4.26.



VMLF110

Description	Size	Cat ref.
10 Way Flush 100A Switch Disconnect Incomer	4	<b>VMLF110</b>
14 Way Flush 100A Switch Disconnect Incomer	5	<b>VMLF114</b>
20 Way Flush 100A Switch Disconnect Incomer	7	<b>VMLF120</b>



### Split Load


**Characteristics:**

- Metal split load and configurable consumer units, single row from 10 to 16 outgoing ways.
- All consumer units contain rear cable entry, along with top & bottom knockouts.
- Supplied with a full metal DIN rail, 100A switch disconnect incomer and 2 Type A RCCBs and a full complement of earth and neutral terminals along with marking labels, busbar, instructions, rear cable protector plate and meter tail clamp.
- Conforms to BS EN 61439-3 including Annex ZB (16kA rating).
- Adjustable depth in wall 72mm-92mm.
- For dimensions see page 4.26.



VMLF910C

Description	Size	Cat ref.
10 Way Flush 100A Switch 2x 100A 30mA Type A RCCB	5	<b>VMLF910C</b> ★
12 Way Flush 100A Switch 2x 100A 30mA Type A RCCB	6	<b>VMLF912C</b> ★
16 Way Flush 100A Switch 2x 100A 30mA Type A RCCB	7	<b>VMLF916C</b> ★



### Configurable



**Characteristics:**

- Metal split load and configurable consumer units with ability to protect selected circuits with RCBOs and the remainder of circuits split across two RCCBs. Single row from 10 to 16 outgoing ways.
- All consumer units contain rear cable entry, along with top & bottom knockouts.
- Supplied with a full metal DIN rail, 100A switch disconnect incomer and 2 Type A RCCBs and a full complement of earth and neutral terminals along with marking labels, busbar, instructions, rear cable protector plate and meter tail clamp.
- References ending in **SPD** come with a Type 2 SPD fitted.
- Conforms to BS EN 61439-3 Including Annex ZB (16kA rating).
- Adjustable depth in wall 72mm-92mm.
- For dimensions see page 4.26.



VMLF910CU

Description	Max Unprotected Ways	Size	Cat ref.
10 Way Flush High Integrity 100A Switch 2x 100A 30mA Type A RCCB	3	5	<b>VMLF910CU</b> ★
12 Way Flush High Integrity 100A Switch 2x 100A 30mA Type A RCCB	3	6	<b>VMLF912CU</b> ★
16 Way Flush High Integrity 100A Switch 2x 100A 30mA Type A RCCB	6	7	<b>VMLF916CU</b> ★
8 Way High Integrity 100A Switch 2x 100A 30mA RCCB Type A with Factory Fitted <b>Surge Protection</b>		5	<b>VMLF908CUSPD</b> ★
10 Way High Integrity 100A Switch 2x 100A 30mA RCCB Type A with Factory Fitted <b>Surge Protection</b>		6	<b>VMLF910CUSPD</b> ★
14 Way High Integrity 100A Switch 2x 100A 30mA RCCB Type A with Factory Fitted <b>Surge Protection</b>		7	<b>VMLF914CUSPD</b> ★



with Surge