

MAIN SWITCH



RATED CURRENT	POLE	PART NUMBERS
100	3	EMS-1003P
	4	EMS-1004P
125	3	EMS-1253P
	4	EMS-1254P

Technical Data

Rated Operational Voltage (Ue)	Category of Duty	Terminal Capacity	Standards
230/400V, 50Hz	AC22B	50mm ²	EN60947-3

RCCB - 4 Pole New



RATED CURRENT	TRIPPING THRESHOLD	PART NUMBERS
100	30mA	RCD10-100/30/4a
	100mA	RCD10-100/100/4a
	100mA time delayed	RCD10-100/100/4s
	300mA	RCD10-100/300/4a

Technical Data

Part No.	Type	Rated Operational Voltage (Ue)	Standard Tripping Time 1 x IΔn	Standard Tripping Time 5 x IΔn	Terminal Capacity	Standards
RCD10-100/30/4a RCD10-100/100/4a RCD-100/300/4a	A	400V, 50Hz	<300ms	<40ms	35mm ²	EN61008-1
RCD10-100/100/4s	S	400V, 50Hz	130-500ms	50 - 150ms	35mm ²	EN61008-1

Where an RCCB is to be used as incoming device, mounting accessory kit TPN-RCCBAK is required (see page 10).