



Miniature circuit breaker (MCB), 10 A, 1p, characteristic: B



Part no. EMBH110
EMBH110

Product name	Eaton Moeller series xPole UK - EM.H MCB
Part no.	EMBH110
EAN	5019586121493
Product Length/Depth	85 millimetre
Product height	73 millimetre
Product width	17.5 millimetre
Product weight	0.111 kilogram
Compliances	RoHS conform
Product Tradename	xPole UK - EM.H
Product Type	MCB
Product Sub Type	None
Public Consumption	Yes
Product Family Description	ES-PMCC-PDC-Eaton Moeller series xPole UK - EM.H MCB
Globally Marketable	No
Countries	United Kingdom of Great Britain and Northern Ireland

Ambient operating temperature - max	55 °C
Ambient operating temperature - min	-25 °C
Amperage Rating	10 A
Application	Switchgear for residential and commercial applications
Built-in depth	70.5 mm
Connectable conductor cross section (multi-wired) - max	25 mm ²
Connectable conductor cross section (multi-wired) - min	1 mm ²
Connectable conductor cross section (solid-core) - max	25 mm ²
Connectable conductor cross section (solid-core) - min	1 mm ²
Current limiting class	3
Degree of protection	IP20
Features	Additional equipment possible
Frequency rating - max	60 Hz
Frequency rating - min	50 Hz
Number of poles	Single-pole
Number of poles (protected)	1
Number of poles (total)	1
Overvoltage category	III
Pollution degree	2
Rated impulse withstand voltage (Uimp)	4 kV
Rated insulation voltage (Ui)	440 V
Rated operational voltage (Ue) - max	240 V
Rated short-circuit breaking capacity (EN 60898) at 230 V	10 kA
Rated short-circuit breaking capacity (EN 60898) at 400 V	10 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 230 V	0 kA
Rated short-circuit breaking capacity (IEC 60947-2) at 400 V	0 kA
Rated switching capacity (IEC/EN 60898-1)	10 kA
Rated switching capacity (IEC/EN 60947-2)	15 kA
Release characteristic	B
Suitable for	Flush-mounted installation
Tripping characteristic	B
Type	EM

		Miniature circuit breaker
Voltage type		AC
Width in number of modular spacings		1

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)

Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ec@ss10.0.1-27-14-19-01 [AAB905014])

Built-in depth	mm	70.5
Release characteristic		B
Number of poles (total)		1
Number of protected poles		1
Rated current	A	10
Rated voltage	V	240
Rated insulation voltage Ui	V	440
Rated impulse withstand voltage Uimp	kV	4
Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V	kA	10
Voltage type		AC
Rated short-circuit breaking capacity Icn according to EN 60898 at 400 V	kA	10
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 230 V	kA	0
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V	kA	0
Frequency	Hz	50 - 60
Current limiting class		3
Flush-mounted installation		Yes
Concurrently switching neutral conductor		No
Over voltage category		3
Pollution degree		2
Additional equipment possible		Yes
Width in number of modular spacings		1
Degree of protection (IP)		IP20
Ambient temperature during operating	°C	-25 - 55
Connectable conductor cross section multi-wired	mm ²	1 - 25
Connectable conductor cross section solid-core	mm ²	1 - 25
Explosion-proof		No