Lot 20 Panel Heaters

- Complies with Lot 20 ERP directive
- Silent operation
- Energy saving 'open window' detection
- Slim line design with 3 sizes available
- Electronic thermostatic control accurate +/- 0.2°C
- Easy to use top mounted customised user-defined LCD display controls
- 7 day electronic programmable controls with backlit display
- 12 pre-set heating profiles
- Splash proof to IP24 for bathrooms or wet areas
- Overheat thermal cut-out
- Supplied with wall fittings
- Suitable for domestic or commercial application
- 2 year replacement warranty



Comfort Heating

Lot 20 Panel Heaters are direct acting heaters, used to heat up a space quickly with 100% efficiency.

Vent-Axia's Panel Heaters offer a range of heat outputs from 1kW to 2kW and every model comes with electronic thermostatic control and 12 pre-set heating programmes. Vent-Axia Panel Heaters look as good as they perform. Stylish and slim, they occupy minimal wall space and are finished in an attractive gloss white finish.

Vent-Axia Panel Heaters are wall mounted and connected to the permanent electrical supply via a fused connection switched outlet. Vent-Axia Panel Heaters are supplied with mounting brackets, 1.5m of flex and come fitted with an easy to use LCD display screen.

Models	
Model	Stock Ref
VAPH1000	495792
VAPH1500	495793

 VAPH 1000
 495/92

 VAPH 1500
 495793

 VAPH 2000
 495794

Adjustable Electronic Thermostat

All Vent-Axia Panel Heaters have a built-in adjustable thermostat offering a full temperature range between 5-30°C, including a 5°C frost protection setting.

For maximum safety there is also a child safety lock and thermal cutout on all models to prevent overheating should the outlet grille be accidentally covered.



Specification

Power			Heating	Heating			Product dimensions mm			Packaged dimensions mm			Product	Gross	
	Model	W	Colour	Setting W	Area m²	Voltage	Approval	Н	W	D	Н	W	D	Weight kg	Weight kg
	VAPH1000	1000		1000	10-13		CE, EMC,	440	455	125	505	520	155	4	5.1
	VAPH1500	1500	White	1500	15-18	230-240V - 50Hz	LVD,RoHS,	440	615	125	505	680	155	5.1	6.3
Ī	VAPH2000	2000	_	2000	20-23	- 30112	ERP	440	775	125	505	840	155	6.55	7.88